





Rev.	ECN	Number	Description	Date	Drawn	Checkd	Approved



RECOMMENDED PCB LAYOUT
TOLERANCE $\pm 0.05\text{MM}$



工作状态

技术要求:

1: 材质: SUS304, 厚度 0.1mm,

2: 表面处理:

整体镀镍 50U'', 镀金 1U''

3: 性能:

3-1. 接触电阻: $50\text{m}\Omega$ MAX.

3-2. 使用温度: $-20^{\circ}\text{C} \sim +65^{\circ}\text{C}$.

3-3. 预压弹力: 0.35N.

3-4. 工作高度位置弹力: 0.8N.

4: 压延毛边 $< 0.05\text{mm}$.

5: 寿命: > 10000 次

6: 包装方式: 载带胶盘包装

DISONG

GENERAL TOLERANCE

XX. ± 0.50	
.X. ± 0.35	.X* $\pm 2.0^{\circ}$
.X ± 0.25	.X* $\pm 1.0^{\circ}$
.XX ± 0.15	.XX* $\pm 0.5^{\circ}$

SCALE: 1:1

UNIT: mm

SIZE: A4

DRAWN Chen

CHECK

APPROVE

DATE 2019. 9. 10

DATE

DATE

DWG. NO.

PARTS NO.(INTENDED USE)

AS-014A

TITLE

(CUSTOMER DRAWING)

Antenna Spring,SMT,
L3.1*W2.0*H1.5mm

REV.

A

SHEET

1/2